



<b>DRIVE PINS</b>		<b>U.S. Anchor Corp*</b>
<b>HxL</b>	<b>Pin Diameter</b>	<b>Minimum Embedment</b>
<b>Head Diameter x Overall Length</b>		
1/4 x 1/2	1/7	3/8
1/4 x 3/4	1/7	5/8
1/4 x 1	1/7	5/8
1/4 x 1 1/4	1/7	5/8
1/4 x 1 1/2	1/7	5/8
1/4 x 2	1/7	5/8
1/4 x 2 1/2	1/7	5/8
1/4 x 3	1/7	5/8

<b>Description</b>	A nail-type fastener with a 3/8" diameter steel washer as an integral part of the nail, approximately 1/3 up the shank of the nail from the point.
<b>Applications/ Advantages</b>	Used to anchor metal, plastic, wood, particle board or fiber board in concrete, block or brick. It doesn't require a pre-drilled hole and can be set with a hammer when using a setting tool designed for drive pins.
<b>Material</b>	Heat treated alloy steel
<b>Anchor Spacing</b>	Anchors should be installed a minimum of ten anchor diameters between each other and a minimum of five anchor diameters from the edge.

\*Drive pin dimensions are based on those originally published by the U.S. Anchor Corporation.