



COUNTERSUNK FINISHING WASHERS				
Screw Size	Outside Diameter	Inside Diameter		Overall Height
	Nominal	Max	Min	
#4	3/8	.150	.120	3/32
#6	15/32	.200	.170	5/64
#8	17/32	.210	.180	7/64
#10	19/32	.265	.235	7/64
#12	21/32	.289	.259	1/8
1/4	25/32	.335	.305	5/32
5/16	15/16	.409	.373	3/16
3/8	1	.460	.425	13/64
3/8	1 1/8	.460	.425	1/4

Description	A formed circular washer designed for use with flat or oval head screws. This is a raised type of finishing washer which is convex shaped. For use with 82° countersunk flat and oval head screws.
Applications/ Advantages	Designed for accommodating the heads of countersunk screws. It provides additional bearing area on the material being fastened and can be used to give a neat, finished appearance.
Material	Steel: Washers shall be punched from hot-rolled, hot-rolled and pickled or cold-rolled steel, or shall be machined from bar stock or tubing, or may be forged at the manufacturer's option. Stainless: 18-8 Stainless Steel
Plating	Steel countersunk finishing washers are typically supplied with a nickel plating. Other coatings such as black oxide are also popular. Stainless washers are usually supplied without additional finish.